

## CLAIMS

1. An electrolytic processing apparatus, comprising:  
a holder for detachably holding a workpiece;  
5 a processing electrode that can come close to or into  
contact with the workpiece held by the holder;  
a feeding electrode for feeding electricity to the  
workpiece held by the holder;  
an ion exchanger disposed in at least one of the space  
10 between the workpiece and the processing electrode and the space  
between the workpiece and the feeding electrode;  
a fluid supply section for supplying a fluid between the  
workpiece and at least one of the processing electrode and the  
feeding electrode, in which the ion exchanger is present;  
15 a power source for applying a voltage between the  
processing electrode and the feeding electrode;  
a drive section for allowing the workpiece held by the  
holder and the processing electrode, facing each other, to make  
a relative movement; and  
20 a numerical controller for effecting a numerical control  
of the drive section.
2. The electrolytic processing apparatus according to  
claim 1, wherein the power source supplies an electric current  
25 or a voltage controlled at a constant value between the  
processing electrode and the feeding electrode.
3. The electrolytic processing apparatus according to  
claim 2, wherein the numerical controller numerically controls  
30 the relative movement speed between the workpiece held by the  
holder and the processing electrode via the drive section.

4. The electrolytic processing apparatus according to claim 2, wherein the numerical controller numerically controls a stop time in a relative step movement of the workpiece held by the holder and the processing electrode via the drive section.

5. An electrolytic processing method, comprising:

providing a processing electrode, a feeding electrode and an ion exchanger disposed in at least one of the space between a workpiece held by a holder and the processing electrode and the space between the workpiece and the feeding electrode;

allowing the processing electrode to be close to or in contact with the workpiece held by the holder while feeding electricity from the feeding electrode to the workpiece;

supplying a fluid to the space between the workpiece and at least one of the processing electrode and the feeding electrode, in which the ion exchanger is present;

applying a voltage between the processing electrode and the feeding electrode; and

allowing the workpiece held by the holder and the processing electrode, facing each other, to make a relative movement while numerically controlling the movement by a numerical controller.

6. The electrolytic processing method according to claim 5, wherein an electric current or a voltage controlled at a constant value is supplied between the processing electrode and the feeding electrode.

7. The electrolytic processing method according to claim 6, comprising:

measuring the form of the workpiece before and/or during processing;

inputting coordinate data on the measured form and on an intended form after processing of the workpiece to the numerical controller; and

5 numerically controlling the relative movement speed between the workpiece held by the holder and the processing electrode according to the coordinate difference between the measured form and the intended form.

8. The electrolytic processing method according to claim 10 6, comprising:

measuring the form of the workpiece before and/or during processing;

15 inputting coordinate data on the measured form and on an intended form after processing of the workpiece to the numerical controller; and

numerically controlling a stop time in a relative step movement of the workpiece held by the holder and the processing electrode according to the coordinate difference between the measured form and the intended form.